## **COUNTRY RUBBLE**



Installation Specifications CSI – 3 Part Spec available at www.CORONADO.com/ArchitecturalResources

## **Choices Specific to Country Rubble**

Standard Colors:	Grey Quartzite, Coastal Brown, Antique Cream, Aspen, Texas Cream, Dakota Brown. Custom colors may be available for an upcharge.
Grout Ioint Width:	Standard ½" Grout Joint, ¾" Grout Joint or Drystacked
	Deep Raked, Drystacked, Full Brushed or Full Tooled
• •	Natural Grey, Natural Off-White or Complementary Color
	Corners, Complementary Tiles, Wall Caps, Post Caps and more. (See Accessories section of binder)
Special Installation Notes	
Pattern:	Stone should be installed in a horizontal ashlar pattern. Do not install stones vertically. Blend the stone on the wall from several different boxes to ensure proper color and size variation. See catalog photos for recommended installation pattern.
Chalk Lines:	Should be used by installer to ensure a straight and level pattern.
Vertical Joints:	Avoid exceeding 2 medium or 3 small stones in height.
Horizontal Joints:	Avoid exceeding 6' to 8' in length.
Sealing:	Not required. However, if installed on an exterior exposed to excessive water from runoff or improper drainage, we suggest the product be sealed in that particular area to protect it from staining or spalling during freeze-thaw cycles.
Freeze-Thaw:	When installing stone in a freeze-thaw environment, extra care should be taken to ensure a full coverage of mortar on the back of each stone, which will prevent water pooling behind the stone after it has been installed.
Drystacked:	A polymer-modified mortar should be used for all drystacked applications.
Installation Info:	Download Coronado's latest installation instructions at www.coronado.com for information on mortar and installation recommendations.
Profile Properties	
Size:	Stone sizes range from 2" to 8" in height and up to 23" in length. Corner returns range from 4" to 10" (nominal).
Thickness:	1" to 2½" (nominal).
Weight:	7 to 10 lbs. per square foot.

Packaging: Available in big boxes (110 sq ft Flats or 100 ln ft Corners) or Dura-Paks (15 sq ft Flats or 12.5 ln ft Corners). When purchasing Country Rubble, coverage is based on installation with a 1/2" joint at the back of the stone. (Note: Square Footage and Linear Footage quantities may vary per region)

1/2" Deep Raked Grout Joint



**COUNTRY RUBBLE** 

COLOR: GREY QUARTZITE

Drystacked



**COUNTRY RUBBLE** 

COLOR: COASTAL BROWN